



TECHNISCHE DATEN	Cocle D x P		DM10	DM10R	DM20	DM20R
MIN/MAX-Produktion	8x8	kg/h	0.06-0.84	0.01-0.5	-	-
	12x8	kg/h	0.07-1.35 0.24-2.8	0.09-1.4	-	-
	16x10	kg/h	0.5-0.6	0.07-2	-	-
	20x12	kg/h	1-11.7	0.2-3.5	-	-
	20x20	kg/h	1.4-17.5	0.6-8.3	-	-
	25x20	kg/h	-	-	2.2-26.5	0.7-11
	30x20	kg/h	-	-	3-39	1.3-18.5
Übersetzungsverhältnis			1:38	1:38	1:38	1:38
Max. Anzahl Komponenten			2	2	2	2
Kapazität Trichter		dm <sup>3</sup>	15	15	15	15
Zentraler Trichter (Optional)		dm <sup>3</sup>	25	25	25	25
Leistung Motor Dosiergerät 230/50-60		kW	0.12	0.12	0.12	0.12
Drehzahl Motor		r.p.m.	3000	3000	3000	3000
Leistung Motor Rührwerk		kW	0.2	0.2	0.2	0.2
Durchsatz Kühlwasser		l/min	-	5	-	5
Kapazität Mischkammer (Optional)		dm <sup>3</sup>	1	5	1	5
Spannung/Frequenz		V/Hz	230/50-60	230/50-60	230/50-60	230/50-60
Schallpegel		dB(A)	<80	<80	<80	<80
Abmessungen LxBxH		mm	331x574x492	331x587x489	330x591x486	332x610x499
Gewicht		kg	19	20	21	21

R: Gekühlte Version